

SIDEWINDER[®] HIGH-IMPACT, WATERPROOF MILITARY LIGHT WITH ARTICULATING HEAD

The Sidewinder meets a variety of hands-free illumination requirements with various color LEDS each with different outputs. 185° articulating head aims the beam. Designed for easy mode selection even with gloved hands.

Meets MIL-STD-810F, METHOD 512.4.



MILITARY	Y MODEL (WHITE, RED, BLUE, IR LEDS)				
PART#	NSN/MCN#	DESCRIPTION	C00	TAA	
14000	6230-01-556-0487	W/ALKALINE—CLAM PACKAGED. COYOTE.	US	YES	
14027	6230-01-571-8752	W/ALKALINE—WITH HELMET MOUNT. CLAM PACKAGED. COYOTE.	US	YES	
14031	-	W/ALKALINE—WITH E-MOUNT. CLAM PACKAGED. COYOTE.	US	YES	

AVIATION MODEL (WHITE, GREEN, BLUE, IR LEDS)					
PART#	NSN/MCN#	N/MCN# DESCRIPTION		TAA	
14008	-	W/ALKALINE — CLAM PACK- AGED. COYOTE.	US	YES	
14024	6230-01-572-6216	W/ALKALINE—WITH HELMET MOUNT. BOXED PACKAGED. COYOTE.	US	YES	

SIDEWINDER® LIGHT OUTPUT & BATTERY RUN TIME						
LED	Light Output	Low 5% Output	Medium 1 25% Output	Medium 2 60% Output	High 100% Output	Strobe 100% Output
White	55 Lumens	100 Hrs+	45 Hrs	11 Hrs	5.5 Hrs	10 Hrs
IR	25mW/sr (min) radiant intensity	200 Hrs+	140 Hrs	60 Hrs	24 Hrs	40 Hrs
Red	1 Lumens	200 Hrs+	140 Hrs	60 Hrs	24 Hrs	40 Hrs
Blue	1.8 Lumens	150 Hrs+	100 Hrs	35 Hrs	16 Hrs	30 Hrs
Green	4.5 Lumens	150 Hrs+	100 Hrs	35 Hrs	16 Hrs	30 Hrs
All run time to 10% of initial output level. Illumination output electronically regulated.						

High-impact super tough nylon construction offers exceptional durability and weather resistance
IPX7 waterproof to 1m for 30 minutes; 3 meter multiple orientation impact resistance tested
2.34" (5.94 cm); 5.02 oz. (142g) [alk]; 4.38 oz. (124g) [lith]
Limited Lifetime Warranty Visit streamlight.com for full warranty information